

BR67 Breaker



BR67



BR67S

Specifications		
ITEM	U.S.A.	METRIC
Input Flow Range	7 – 9 gpm	26 – 34 lpm
Input Pressure	1500 – 2000 psi	105 – 140 bar
Max. Back Pressure	250 psi	17 bar
Optimum Flow	8 gpm	30 lpm
BR67		
Steel Capacity	6 (15.2 cm) x 1-1/8 Hex & 6 (15.2 cm) x 1-1/4 in. Hex	
Weight	67 lbs.	30 kg
Length	27 in.	68 cm
Width (at handles)	16 in.	41 cm
BR67S		
Steel Capacity	6 (15.2 cm) x 1-1/8 Hex & 6 (15.2 cm) x 1-1/4 in. Hex	
Weight	75 lbs.	34 kg
Length	29 in.	73 cm
Width (at handles)	18 in.	46 cm
Porting	8 SAE O-Ring	
Connector	3/8 in. Male Pipe Hose End	

Features and Benefits

Stanley's line of handheld breakers is the largest in the world, with a wide selection of models suited to virtually any application. The **BR67** and **BR67S** are medium-duty tools for work in the 70-90 pound class. They are highly productive in utility construction, street maintenance, repair of water and gas mains, and general contracting jobs. Available in both a T-Handle and Anti-Vibration Handle Model. Spring-Dampened, Anti-Vibration Handles (**BR67S**) reduce operator fatigue, allowing the breaker to float in the user's hands. Built in handle stops allow operator to apply full body weight in tough applications. Easi-Ride™ foot, offered on the **BR67**, absorbs and controls tool-bit bounce, greatly reducing operator fatigue. Feathering On/Off Valve controls blow speed, making startup and initial tool placement easy. Diaphragm Accumulator provides trouble-free operation with system back pressures up to 250 psi (17 bar). Accumulator on **BR67S** can be serviced without disassembling the tool. Both models operate on open-center systems and are available in 1-1/8 or 1-1/4 in. chuck hex sizes.



639 Manhattan Blvd.
 Harvey, LA 70058 USA
 TEL: (504) 362-8124
 FAX: (504) 362-3600
www.aquaairind.com
 EMAIL sales@aquaairind.com

BR67 Breaker Cont.

Accessories	
PART NO.	DESCRIPTION
1 1/8 in. Hex x 6 in. Shank	
02331	Clay Spade, 5-1/2 in. (14 cm) blade
02332	Asphalt Cutter, 5 in. (12.7 cm) blade x 11 in. (28 cm) *
02333	Moil Point, 14 in. (35.6 cm) *
02334	Chisel, 3 in. (76 mm) blade x 14 in. (35.6 cm) *
03990	Chisel Point, 14 in. (35.6 cm) *
04176	Ground Rod Driver, 1 in. (25 mm) rod
08106	Asphalt Wedge, 12 in. (30.5 cm) *
08107	Keen Kut, 16 in. (40.6 cm) *
1 1/4 in. Hex x 6 in. Shank	
02335	Asphalt Cutter, 5 in. (12.7 cm) blade x 11 in. (28 cm) *
02336	Moil Point, 14 in. (35.6 cm) *
02337	Chisel, 3 in. (76 mm) blade x 14 in. (35.6 cm) *
02338	Heavy Duty Chisel, 1 in. (25 mm) x 14 in. (35.6 cm) *
04367	Ground Rod Driver, 1 in. (25 mm) rod
04404	Heavy Duty Moil Point, 18 in. (45.7 cm) *
04405	Clay Spade, 8 in. (20.3 cm) blade
08118	Brick Wedge
18119	Asphalt Wedge
09262	Clay Spade, 5-1/2 in. (14 cm)
17782	Detachable Shank (requires no. 17783)
17783	Tamping Pad, 6 in. (15.2 cm) pad (requires no. 17782)

* Length measured from bottom tip of tool to bottom surface of collar.

Test Equipment	
PART NO.	DESCRIPTION
02835	Accumulator Tester
03189	20 gpm (75 lpm) Flow Meter
04182	Flow and Pressure Tester
06545	Accumulator Charge Kit

BR67 Breaker Cont.

Model Numbers	
MODEL	DESCRIPTION
BR67120	BR67 T-Handle Breaker, 1-1/8 in. Hex
BR67120E	BR67 T-Handle Breaker, 1-1/8 in. Hex, Easi-Ride Foot
BR67130	BR67 T-Handle Breaker, 1-1/4 in. Hex
BR67130E	BR67 T-Handle Breaker, 1-1/4 in. Hex, Easi-Ride Foot
BR67320	BR67 Underwater T-Handle Breaker, 1-1/8 in. Hex
BR67330	BR67 Underwater T-Handle Breaker, 1-1/4 in. Hex
BR67125	BR67S Anti-Vibration Handle Breaker, 1-1/8 in. Hex
BR67135	BR67S Anti-Vibration Handle Breaker, 1-1/4 in. Hex

Note: All models listed above ship with hose whips.

Service Tools	
PART NO.	DESCRIPTION
04596	Seal Kit
04908	Split Ring (Auto Valve Removal)
04909	Spacer (Flow Sleeve Install)
04910	Flow Sleeve Removal Tube
05508	Accumulator Disassembly Tool
05640	Accumulator Cylinder Puller

