

GR 29 U/W Grinder



Features and Benefits

Stanley's Underwater GR29 Grinder can be used for grinding and cleaning with either cup or standard grinding wheels, wire or nylon brushes. The Integral Stanley Hyrevz™ gear motor is manufactured to exacting standards to deliver maximum efficiency. The plastisol covering the handle transmits very little heat. The plastisol gives a more comfortable grip to the tool.

There are two positions available for the assist handle to be conveniently placed by the operator. Either position is at a most comfortable handling position from the valve handle. The wheel guard is adjustable. By loosening the clamp screw the guard may be rotated to any convenient position.

Specifications		
ITEM	U.S.A.	METRIC
Capacity	9 in. Wheel on 5/8 in. – 11 Arbor	
RPM	2700 @ 10 gpm	2700 @ 38 lpm
Weight (with guard)	14 lb.	6.4 kg
Length	11 in.	28 cm
Width (with guard)	12 in.	30.5 cm
Pressure	1000-2500 psi	70-176 bar
Flow Range	4-10 gpm	15-38 lpm
Optimum Flow	10 gpm	38 lpm
Porting	-8 SAE O-Ring	
Hose Whips	No	
Motor	Stanley Hyrevz™ Gear	



639 Manhattan Blvd.
Harvey, LA 70058 USA
TEL: (504) 362-8124
FAX: (504) 362-3600
www.aquaairind.com
EMAIL sales@aquaairind.com

GR 29 U/W Grinder

Ordering Information	
MODEL	DESCRIPTION
GR29310	Grinder, Underwater, less couplers
GR2930101	Grinder, Underwater, couplers, CE

Accessories	
PART NO.	DESCRIPTION
02587	Grinding wheel for Metal, 9-inch diameter x 5/8-11 thread
02588	Grinding wheel for Masonry, 9-inch diameter x 5/8-11 thread
03691	Grinding wheel, 7-inch diameter x 5/8-11 thread
05194	Adapter, 5/8-11 thread, depressed center wheel